1. (Currently Amended) A bone marker for use in image guided surgery, comprising:

\_\_\_\_\_\_ a support having an anchor mechanism for anchoring the support in a bone, the

bone marker further comprising at least one reference member detectable by an image guided system, the at least one reference member being attached to the support, in which wherein the support comprises at least one limb that which is resiliently deformable.

- 2. (Currently Amended) <u>The A-bone marker of as claimed in claim 1, wherein in which</u> the support further comprises at least one limb which is rigid.
- 3. (Currently Amended) A bone marker as claimed in The bone marker of claim 1, wherein the in which a resiliently deformable limb comprises a tightly wound helical spring.
- 4. (Currently Amended) A bone marker as claimed in The bone marker of claim 3, wherein the spring has in which the flat abutting surfaces of the wire are flat.
- 5. (Currently Amended) A bone marker as claimed in The bone marker of claim 1, wherein in which a resiliently deformable limb is made from a damped elastomer.
- 6. (Currently Amended) A bone marker as claimed in The bone marker of claim 1, in which a wherein the resiliently deformable limb is made from a shape memory alloy.
- 7. (Currently Amended) A bone marker as claimed in The bone marker of claim 1, in which wherein the ratio of the outer diameter of the a resiliently deformable limb to its inner diameter is at most 3:1.
- 8. (Currently Amended) A bone marker as claimed in The bone marker of claim 1, in which wherein the anchor mechanism comprises at least one fixation member for anchoring the bone marker in the bone, and a coupling member for coupling the support to the fixation member.

Serial No. 10/567,235 DEP5167USPCT

9. (Currently Amended) A bone marker as claimed in The bone marker of claim 8, in which wherein the coupling member is adjustable to allow rotation of the support about the fixation member.

- 10. (Currently Amended) A bone marker as claimed in The bone marker of claim 8, in whichwherein the at least one fixation member is a threaded screw.
- 11. (Currently Amended) A bone marker as claimed in The bone marker of claim 10, in whichwherein the diameter of the threaded screw is not more than about 2 mm.
- 12. (Currently Amended) A bone marker as claimed in The bone marker of claim 1, in which wherein the reference members transmit signals.
- 13. (Currently Amended) A bone marker as claimed in The bone marker of claim 1, wherein the reference members reflect signals.
- 14. (Cancelled)